

Giotto

Complete line of road barriers



tuned to you

Technical features

	GIOTTO 30 BT	GIOTTO 30S BT	GIOTTO 50 BT	GIOTTO 50S BT
Control unit	LIBRA C G	LIBRA C GS	LIBRA C G	LIBRA C GS
Power supply	230V	230V	230V	230V
Motor power supply	24V	24V	24V	24V
Power input	250W	300W	250W	300W
Opening or closing time	4sec	2.5sec	5sec	4sec
Type of limit switch	electronic open/close	electronic open/close	electronic open/close	electronic open/close
Slowdown	adjustable	adjustable	adjustable	adjustable
Impact reaction	Encoder	Encoder	Encoder	Encoder
Locking	Mechanical	Mechanical	Mechanical	Mechanical
Release	personal release key	personal release key	personal release key	personal release key
Frequency of use	Semi-intensive	Intensive	Semi-intensive	Intensive
Environmental conditions	from -20°/-40 with acc. THERMO)°C to 55°C			
Actuator weight	40kg	41kg	41kg	42kg


Giotto



- Barriers for intensive use capable of operating working passages up to 5 metres.
- Available in 24V versions, with a wide range of accessories making them ideal for any context.




((ER-Ready))



DESCRIPTION	VOLTAGE	USEFUL PASSAGE
	(V)	m
GIOTTO 30 BT P940040 00002	24	3
GIOTTO 30S BT P940042 00002	24	3
GIOTTO 50 BT P940041 00002	24	5
GIOTTO 50S BT P940043 00002	24	5

Table for balancing boom with accessories

GIOTTO BT /GIOTTO S BT		Accessori: lunghezza utile asta e bilanciamento. / Accessories: working length of boom and balancing. / Accessoires: longueur utile de la barre et équilibrage. Zubehör: Nutzlänge Schranke und Auswuchtung. / Accesorios: longitud útil mástil y balance. / Accessoires: nuttige lengte slagboom en balancerling.																			
	SB		+ SB	+ SB								+ SB	+ SB								
	PCA (above boom only)		+ PCA	+ PCA	+ PCA	+ PCA	+ PCA	+ PCA	+ PCA			+ PCA	+ PCA	+ PCA	+ PCA	+ PCA	+ PCA	+ PCA	+ PCA		
	PCA (below boom only)							+ PCA	+ PCA								+ PCA	+ PCA			
	KIT GTO LIGHT		+ LIGHT			+ LIGHT						+ LIGHT			+ LIGHT		+ LIGHT				
	GAM		+ GAM	+ GAM	+ GAM	+ GAM	+ GAM	+ GAM	+ GAM	+ GAM	+ GAM										
	BIR					+ BIR	+ BIR	+ BIR							+ BIR	+ BIR	+ BIR				
	MIN L		3,2 m	3,2 m	3,3 m	3,7 m	3,8 m	4 m	4,2 m	4,3 m	4,5 m	4,8 m	3,4 m	3,4 m	3,6 m	4,1 m	4,2 m	4,4 m	4,6 m	4,7 m	5 m
	MAX L		3,5 m	3,6 m	3,7 m	4,2 m	4,3 m	4,5 m	4,7 m	4,8 m	5 m	5 m	3,8 m	3,8 m	4 m	4,5 m	4,6 m	4,9 m	5 m	5 m	5 m
	MIN L	4,4 m	2,4 m	2,5 m	2,6 m	2,9 m	2,9 m	3,1 m	3,2 m	3,3 m	3,5 m	3,7 m	2,7 m	2,7 m	2,8 m	3,2 m	3,3 m	3,4 m	3,6 m	3,7 m	3,9 m
	MAX L	5 m	3,3 m	3,3 m	3,5 m	3,9 m	4 m	4,2 m	4,3 m	4,4 m	4,7 m	5 m	3,5 m	3,5 m	3,7 m	4,2 m	4,3 m	4,5 m	4,7 m	4,9 m	5 m
	MIN L		2,4 m	2,5 m	2,5 m	2,9 m	2,9 m						2,7 m	2,7 m	2,8 m						
	MAX L		2,7 m	2,7 m	2,8 m	3 m	3 m						2,9 m	2,9 m	3 m						
	MIN L		1,9 m	2 m	2 m	2,3 m	2,3 m	2,5 m	2,5 m	2,6 m	2,8 m	2,9 m	2,2 m	2,2 m	2,3 m	2,6 m	2,7 m	2,8 m	2,9 m		
	MAX L		2,3 m	2,3 m	2,4 m	2,7 m	2,8 m	2,9 m	3 m	3 m	3 m	3 m	2,5 m	2,5 m	2,6 m	3 m	3 m	3 m			
	MIN L	2,1 m	1 m	1,1 m	1,1 m	1,2 m	1,3 m	1,3 m	1,4 m	1,4 m	1,5 m	1,6 m	1,3 m	1,3 m	1,3 m	1,5 m	1,6 m	1,7 m	1,7 m	1,8 m	1,9 m
	MAX L	3 m	1,9 m	2 m	2 m	2,3 m	2,3 m	2,5 m	2,5 m	2,6 m	2,8 m	2,9 m	2,2 m	2,2 m	2,3 m	2,6 m	2,7 m	2,8 m	2,9 m	3 m	3 m



L: Working boom length.

Accessories

AQG3

Complete 3 metre rectangular boom.



N728033

AQG5

Complete 5 metre rectangular boom.



N728034

GTO AQG

Pack of accessories for installation of 3/5 m rectangular boom.



N999507

ATG3

Complete 3 metre round boom.



N728031

ATG5

Complete 5 metre round boom.



N728032

GTO ATG

Pack of accessories for installation of 3/5 m rectangular boom



N999513

**MOOVI
ART 90**

90° joint, working passage max 4 m, for rectangular booms only.



N728029

MOOVI GA

Mobile support rod for AQG or ATG booms.



D940008

MOOVI GAMA

Dampened mobile support rod for AQG or ATG booms.



D940009

FAF

Fixed rest fork for booms.



D730088

SB

Aluminium fencing for booms



D573003

PCA B 3

Red rubber profile
3 metres



P120019 00001

PCA B 6

Red rubber profile
6 metres



P120019 00002

BIR C


Rubber strip for protection
and safety
(h 30mm)



N190104

CBO

Anchoring base



D730251

KIT MOOVI LIGHT

Lights on boom from 3 to 4.5 m



P120001 00001

KIT MOOVI LIGHT 1


Lights on boom size 5 m



P120001 00002

MOOVI BAT

Set of buffer batteries for Giotto



P120017

THERMO)


Thermostated heating element for using the barriers to ambient temperatures of -40°C



P120018

KIT MOOVI 130

Support for fitting Cellula 130 on Giotto enclosure in line with boom



P120002

SCS 1

Serial board for zone connection and opposing barriers



P111376

Bft Spa

Via Lago di Vico, 44

36015 Schio (VI)

T +39 0445 69 65 11

F +39 0445 69 65 22

→ www.bft.it