

	220/CL 600A	275/CL 600A
MOVING CYLINDER	FE 370 STEEL (IRON) – AISI 304 STAINLESS STEEL	
MOVING CYLINDER NOMINAL DIAMETER	220 mm	275 mm
MOVING CYLINDER HEIGHT	600 mm	
MOVING CYLINDER FE 370 STEEL THICKNESS	4 mm	5 mm
MOVING CYLINDER STAINLESS STEEL THICKNESS	AISI 304 :4 mm	-
MOVING CYLINDER FE 370 STEEL FINISH	POLYESTER POWDER PAINT – STANDARD GREY ANTHRACITE	
MOVING CYLINDER STAINLESS STEEL FINISH	AS ABOVE, OR BRUSHED	-
REFLECTING ADHESIVE STRIP	YES - HEIGHT 55 mm	
RISE SPEED	7 cm/sec	
LOWERING SPEED	20 cm/sec	
AUTOMATIC EMERGENCY LOWERING	YES	
SAFETY REVERSAL PRESSURE SWITCH	YES	
CONNECTION LINE TO CONTROL UNIT	STANDARD 10 mt (MAXIMUM LENGTH: 20 mt)	STANDARD 20 mt
PNEUMATIC COMPRESSOR HANDLING	IN THE CONTROL UNIT	
PNEUMATIC SOLENOID VALVE	BUILT-IN INTO THE PILOMAT	
GRADE OF PROTECTION	IP 67	
TYPE OF USE	INTERMITTENT (300 OPERATIONS/DAY +/- 10%)	
IMPACT RESISTANCE (WITHOUT DEFORMATION)	30.000 J	40.000 J
BREAKOUT RESISTANCE	150.000 J	200.000 J
OPERATING TEMPERATURE	- 10°C + 60° C	
NOMINAL PILOMAT WEIGHT (WITHOUT PIT)	65 kg	80 kg
NOMINAL WEIGHT OF STANDARD PIT, WITH COUNTER-FRAME AND BRACKETS	34 kg	40 kg

